

AF/ IFW

PTO/SB/21 (09-04)

Approved for use through 07/31/2006. OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**TRANSMITTAL
FORM**

(to be used for all correspondence after initial filing)

Total Number of Pages in This Submission

35

Application Number	10/824,016
Filing Date	April 13, 2004
First Named Inventor	Dana Lee and Bomy Chen
Art Unit	2822
Examiner Name	Kiesha L. Rose
Attorney Docket Number	351913-992472

ENCLOSURES (Check all that apply)

- | | | |
|--|--|---|
| <input type="checkbox"/> Fee Transmittal Form
<input type="checkbox"/> Fee Attached
<input type="checkbox"/> Amendment/Reply
<input type="checkbox"/> After Final
<input type="checkbox"/> Affidavits/declaration(s)
<input type="checkbox"/> Extension of Time Request
<input type="checkbox"/> Express Abandonment Request
<input type="checkbox"/> Information Disclosure Statement
<input type="checkbox"/> Certified Copy of Priority Document(s)
<input type="checkbox"/> Response to Missing Parts/ Incomplete Application
<input type="checkbox"/> Response to Missing Parts under 37 CFR 1.52 or 1.53 | <input type="checkbox"/> Drawing(s)
<input type="checkbox"/> Licensing-related Papers
<input type="checkbox"/> Petition
<input type="checkbox"/> Petition to Convert to a Provisional Application
<input type="checkbox"/> Power of Attorney, Revocation Change of Correspondence Address
<input type="checkbox"/> Terminal Disclaimer
<input type="checkbox"/> Request for Refund
<input type="checkbox"/> CD, Number of CD(s) _____
<input type="checkbox"/> Landscape Table on CD | <input type="checkbox"/> After Allowance Communication to TC
<input type="checkbox"/> Appeal Communication to Board of Appeals and Interferences
<input type="checkbox"/> Appeal Communication to TC (Appeal Notice, Brief, Reply Brief)
<input type="checkbox"/> Proprietary Information
<input type="checkbox"/> Status Letter
<input checked="" type="checkbox"/> Other Enclosure(s) (please identify below):
1. Amended Appeal Brief (+2)
2. Return postcard |
|--|--|---|
- Remarks**
The Commissioner is hereby authorized to charge any additional fees which may be required or credit any overpayment to Deposit Account 07-1896. A duplicate copy of this sheet is enclosed.
Customer No. 26379

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT

Firm Name	DLA Piper Rudnick Gray Cary US LLP		
Signature			
Printed name	Ronald L. Yin		
Date	August 10, 2006	Reg. No.	27,607

CERTIFICATE OF TRANSMISSION/MAILING

I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below.

Signature			
Typed or printed name	Jan Huss	Date	August 10, 2006

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

American LegalNet, Inc.
www.USCourtForms.com

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of

Dana Lee and Bomy Chen

Application No. 10/824,016

Filed: April 13, 2004

For: METHOD OF MANUFACTURING AN
ISOLATION-LESS ARRAY OF BI-
DIRECTIONAL READ/PROGRAM NON-
VOLATILE FLOATING GATE
MEMORY CELLS WITH
INDEPENDENT CONTROLLABLE
CONTROL GATES

Group Art Unit: 2822

Examiner: Rose, Kiesha L.

AMENDED APPEAL BRIEF

2000 University Avenue
East Palo Alto, CA 94303-2248
(650) 833-2000

Technology Center: 2800


Control Number: 10/824,016



Mail Stop Appeal Brief-Patents
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Certificate of Mailing

I hereby certify that this correspondence is being
deposited with the United States Postal Service with
sufficient postage as FIRST CLASS MAIL in an
envelope addressed to: Mail Stop Appeal Brief-
Patents, Commissioner for Patents, P.O. Box 1450,
Alexandria, VA 22313-1450, on:
August 10, 2006



Jan Huss

Dear Sir/Madam:

This is an amended brief for an appeal from a Final Office Action dated February 10, 2006, and from a Notice of Appeal that was filed on May 9, 2006, and is in response to the Notification of non-Compliant Appeal Brief, mailed on August 3, 2006.

TABLE OF CONTENTS

	<u>Page</u>
Real Party in Interest.....	1
Related Appeals and Interferences.....	1
Status of Claims	1
Status of Amendments	1
Summary of Claimed Subject Matter	1
Grounds of Rejection to be Reviewed on Appeal.....	2
Argument	2
Conclusion	4
Claims Appendix	5
Evidence Appendix	8
Related Proceedings Appendix	9



Real Party in Interest

The real party of interest is Silicon Storage Technology, Inc., pursuant to the assignment executed on April 7, 2004, and recorded on April 13, 2004 at reel 015220 and frame 0338.

Related Appeals and Interferences

There are no related appeals or interferences.

Status of Claims

Claims 1-11 were originally presented on the filing of the application. This is an appeal of the rejected Claims 1-11.

Status of Amendments

No amendments were filed subsequent to final rejection.

Summary of Claimed Subject Matter

Applicants' invention, as claimed, deals with a method of making an isolation-less array of non-volatile memory cells in a semiconductor substrate. Specifically, the term "isolation-less" means that no Field Oxide or Shallow Trench Isolation (STI) is used between adjacent rows (or columns) of memory cells. In independent claim 1, the method of making an isolation-less array is disclosed in paragraph 2 (hereinafter [0002]), page 1. The semiconductor substrate is shown in Figure 2A as element 20. The step of forming a plurality of spaced apart trenches is shown in Figure 2C as element 28 and is described in [0013], page 4. The step of forming a pair of floating gates in each trench is shown in Figure 2D as element 34 and is described in [0014],

page 4. The step of forming a first terminal is shown in Figure 2D as element 32 and is described in [0017], page 4. The step of forming a control gate is shown in Figure 2E as element 38 and is described in [0018], page 5. The step of forming a conductor on the planar surface is shown in Figure 2G as element 60 and is described in [0020], page 6. The transistors formed are transistors 11 shown in Figure 1 and described in [0019], page 6. The step of patterning is described in [0020], page 6. Finally the step of cutting each pair of floating gates is shown in Figure 2H where element 34 is cut and is described in [0021], page 6.

Grounds of Rejection to be Reviewed on Appeal

The sole ground of rejection to be reviewed on appeal is whether Claims 1-11 were properly rejected under 35 U.S.C. §102(b) as being anticipated by U.S. Patent 6,541,815 (“Mandelman”).

Argument

In rejecting claims 1-11, the examiner alleged, without any support, that Mandelman discloses “a conductor (58) on planar surface, which is spaced apart from the planar surface and serves as a gate for a transistor between adjacent transistors.” Applicants respectfully disagree.

In Mandelman, the conductor 58 extends over a source/drain region 50 which is in the top planar surface of the substrate. See Fig. 2A. In fact as seen in Figure 2A, the function of the conductor 58 is to be capacitively coupled to the floating gate. As a result, the conductor 58 cannot function as a “gate for a transistor between adjacent trenches”, as required by claim 1. Accordingly for at least this reason, the rejection of Claim 1 based upon Mandelman is in error.

Furthermore, with respect to claim 1, claim 1 recites that the control gate which is formed is “continuous in said first direction.” For the reasons set forth hereinafter, in response to the rejection of claim 5, the control gate of Mandelman is not continuous in the first direction. A review of Mandelman shows that the so-called control gate 44 is used only to connect to the word line 60 (see fig. 16B). Thus, contrary to the requirement of Claim 1, the control gate 44 of Mandelman is not continuous in the first direction.

In rejecting claims 3-4 and 10-11, the examiner asserted, without any proof, that Mandelman “teaches that the floating gates are etched and would naturally leave somewhat rounded ends and has a tip along the floating gates at an end closest to the bottom of the trench and tip that is furthest away from the bottom wall.”

Applicants respectfully note that Mandelman does not teach either rounding or tipped ends of a floating gate. The floating gates 30 disclosed by Mandelman are substantially rectilinear in shape. See Figure 1, 2A-2C, 7, 8, 9, 10, 11, 12B, 14B, 15B, 16B, and 17B. None of the floating gates 30 shown in any of these figures displays either a rounded end or an end with a tip. Thus, Applicants respectfully traverse this aspect of the rejection.

With respect claim 5, the examiner asserted that Mandelman “teaches the floating gates are etched and the control gates need not be etched. (Columns 7 and 8)” Applicants respectfully traverse this rejection.

A review of Columns 7 and 8 fails to demonstrate that it teaches the etching of the floating gates without etching the control gates. In fact, a review of Figure 15A shows the contrary. The control gate 44 is shown as being disjointed and discontinuous. Therefore, contrary to the examiner’s assertion, the control gates appear to be etched at the same time that

floating gates are cut. See also Figures 12C and 13 wherein the control gate 44 is not present in those joints. Therefore, the assertion by the examiner is strenuously objected.


Conclusion

For all of the reasons set forth hereinabove, Applicants respectfully submit that the claims appended hereto are patentable and urge a reversal of the final rejection.

Respectfully submitted,

DLA Piper Rudnick Gray Cary US LLP

Dated: August 10, 2006

By: 
Ronald L. Yin
Reg. No. 27,607
Attorney for Applicant(s)

ATTN: Patent Department
DLA Piper Rudnick Gray Cary US LLP
2000 University Avenue
East Palo Alto, CA 94303-2248
Tel: (650) 833-2000
Fax: (650) 833-2001
ronald.yin@dlapiper.com

Claims Appendix

1. A method of making an isolation-less array of non-volatile memory cells in a semiconductor substrate, having a planar surface; said substrate is of a first conductivity type comprising;

forming a plurality of spaced apart trenches in said planar surface of said substrate in a first direction, each trench having a first sidewall, a second sidewall and a bottom wall;

forming a pair of floating gates along the first and second sidewalls in each trench, each floating gate spaced apart from the first and second sidewalls, respectively;

forming a first terminal of a second conductivity type along the bottom wall of each trench in the substrate;

forming a control gate in each trench; each control gate insulated from and capacitively coupled to the floating gates in the trench and insulated from the first terminal along the bottom wall of the trench, wherein each control gate is continuous in said first direction;

forming a conductor on said planar surface, said conductor spaced apart from said planar surface, wherein said conductor serving as a gate for a transistor between adjacent trenches;

patterning said conductor along a second direction substantially perpendicular to said first direction to form a plurality of spaced apart strips of conductors, with an opening between each pair of conductor strips; and

cutting each pair of floating gates in each trench.

2. The method of claim 1 wherein the step of forming a pair of floating gates comprises:

forming a layer of silicon dioxide along said first sidewall, said second sidewall, and said bottom wall of each trench;

depositing a layer of polysilicon along said silicon dioxide of said first sidewall, said second sidewall and said bottom wall of each trench;

anisotropically etching said layer of polysilicon, to remove said layer of polysilicon from said bottom wall, forming a pair of polysilicon floating gate spacers along the first and second sidewalls in each trench.

3. The method of claim 2 further comprising the step of forming a tip along each of said floating gates at an end closest to said bottom wall in each trench.
4. The method of claim 2 further comprising the step of forming a tip along each of said floating gates at an end furthest away from said bottom wall in each trench.
5. The method of claim 1 wherein said cutting step cuts each pair of floating gates through said opening in each trench without cutting the control gate.
6. The method of claim 2, wherein said step of forming a plurality of spaced apart trenches in said planar surface further comprises:
 - applying a layer of masking material on said planar surface of said substrate;
 - patterning said masking material in said first direction to form a plurality of masking strips and a plurality of first openings with a first opening between each pair of masking strips;
 - etching said substrate to form said plurality of trenches through said first openings.
7. The method of claim 6 wherein the masking material is silicon nitride.
8. The method of claim 1 wherein said cutting step is performed prior to said control gate being formed in each trench.
9. The method of claim 8 wherein the step of forming a pair of floating gates comprises:
 - forming a layer of silicon dioxide along said first sidewall, said second sidewall, and said bottom wall of each trench;
 - depositing a layer of polysilicon along said silicon dioxide of said first sidewall, said second sidewall and said bottom wall of each trench;
 - anisotropically etching said layer of polysilicon, to remove said layer of polysilicon from said bottom wall, forming a pair of polysilicon floating gate spacers along the first and second sidewalls in each trench.

10. The method of claim 9 further comprising the step of forming a tip along each of said floating gates at an end closest to said bottom wall in each trench.

11. The method of claim 9 further comprising the step of forming a tip along each of said floating gates at an end furthest away from said bottom wall in each trench.

BEST AVAILABLE COPY

Evidence Appendix

None

Related Proceedings Appendix

None